

7955111

PDU Basic 32A/1P CEE 24xC13 / 4xC19



Technical

Description	Robust, compact basic power distributor for the IT environment. Thanks to the compact PDU, any IT rack may be easily equipped with a professional power distribution system. With the TS IT rack, assembly is even tool-free. The compact design allows simple assembly.
Material	Aluminium section, black anodised
Protection category IP to IEC 60 529	IP 20
Design	PDU Basic
To fit	TS IT TS 8 Height: 1800 mm
Dimensions	Width: 44 mm Depth: 62 mm Length: 1115 mm
Rated current (max.)	32 A
Type of electrical connection	CEE
Length of connection cable	3 m
Sockets	24 x IEC 320 socket C13 - Black 4 x IEC 320 socket C19 - Black
Standards	EN 60 950-1
Directives	EMC Directive 2014/30/EU Low Voltage Directive 2014/35/EU
Infeeds	Qty.: 1 Phases per infeed: 1~
Ambient conditions	Operating temperature: +0°C...+45°C Storage temperature: -25°C...+70°C Ambient humidity (non-condensing): 10 % - 95 %
Circuit-breaker 16 A (qty.)	2
Packs of	1 pc(s).
Weight/pack	4.09 kg
EAN	4028177684928
Customs tariff number	85369085

ETIM 6.0	EC000330
ETIM 5.0	EC002762
eCl@ss 8.0/8.1	27142604
eCl@ss 7.0/7.1	27142604
eCl@ss 6.0/6.1	27142604
eCl@ss 5.1/5.1.4	27143401

Datasheet generated from <https://onetimepim.com> last updated Thursday, January 23, 2020 11:01:14 AM