



APC Smart-UPS SRT 10000VA 230V SRT10KXLI

Call for More Information 04 7099333

- High density, double-conversion on-line power protection with scalable runtime
- Includes: CD with software, Documentation CD, Installation guide, Temperature Probe, USB cable, Warranty card, Web/SNMP Management Card

Output	
Output power capacity	10.0kWatts / 10.0kVA
Max Configurable Power (Watts)	10.0kWatts / 10.0kVA
Nominal Output Voltage	230V
Output Voltage Distortion	Less than 2%
Output Frequency (sync to mains)	50/60Hz +/- 3 Hz
Other Output Voltages	220, 240
Load Crest Factor	3 : 1
Topology	Double Conversion Online
Waveform type	Sine wave
Output Connections	(6) IEC 320 C13 (Battery Backup) (4) IEC 320 C19 (Battery Backup) (1) Hard Wire 3-wire (H N + G) (Battery Backup) (3) IEC Jumpers (Battery Backup)
Bypass	Internal Bypass (Automatic and Manual)


Input	
Nominal Input Voltage	230V, 400V 3PH
Input frequency	40 - 70 Hz (auto sensing)
Input Connections	Hard Wire 3 wire (1PH+N+G), Hard Wire 5-wire (3PH + N + G)
Input voltage range for main operations	160 - 275V
Input voltage adjustable range for mains operation	100 - 275 (half load), 173 - 476 (half load)V
Other Input Voltages	220, 240, 380, 415

Disclaimer: Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.

Technical Specifications

APC Smart-UPS SRT 10000VA 230V | SRT10KXLI | Downloaded on 05/24/2020 (EST)

Batteries & Runtime

Battery type	Maintenance-free sealed Lead-Acid battery with suspended electrolyte : leakproof
Typical recharge time	1.5hour(s)
Nominal Battery Voltage	+/-192 V (split battery referenced to neutral)
Replacement Battery	APCRBC140 
Expected Battery Life (years)	3 - 5
RBC Quantity	2
Extendable Run Time	1
Battery Volt-Amp-Hour Capacity	1805
Extended Run Options	APC-Smart-UPS-SRT-10000VA-230V (Available in Technical Tab on site)
Runtime	View Runtime Graph (Available in Technical Tab on site) View Runtime Chart (Available in Technical Tab on site)
Efficiency	View Efficiency Graph (Available in Technical Tab on site)

Communications & Management

Interface Port(s)	RJ-45 10/100 Base-T, RJ-45 Serial, Smart-Slot, USB
Control panel	Multi-function LCD status and control console
Audible Alarm	Audible and visible alarms prioritized by severity
Emergency Power Off (EPO)	Yes
Available SmartSlot™ Interface Quantity	1

Surge Protection and Filtering

Surge energy rating	480Joules
---------------------	-----------

Physical

Maximum Height	432MM, 43.2CM
Maximum Width	263MM, 26.3CM
Maximum Depth	715MM, 71.5CM
Net Weight	111.82KG
Shipping weight	126.82KG
Shipping Height	461MM, 46.1CM
Shipping Width	600MM, 60.0CM

Disclaimer: Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.

Technical Specifications

Physical

Shipping Depth	1000MM, 100.0CM
Color	Black

Environmental

Operating Temperature	0 - 40 °C
Operating Relative Humidity	0 - 95 %
Operating Elevation	0-3000meters
Storage Temperature	-15 - 45 °C
Storage Relative Humidity	0 - 95% non-condensing %
Storage Elevation	0-15000meters
Audible noise at 1 meter from surface of unit	55.0dBA
Online thermal dissipation	1947.0BTU/hr
Protection Class	IP 20

Conformance

Approvals	CE, CE Mark, EAC, EN/IEC 62040-1, EN/IEC 62040-2, IRAM, RCM, VDE
Standard warranty	3 years repair or replace (excluding battery) and 2 years for battery

Sustainable Offer Status

RoHS	Compliant
REACH	REACH: Contains SVHCs

Disclaimer: Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.