

Lock



Features

- Name: cabinet lock.
- Specifications: round lock (optional).
- Surface treatment: spray.
- Characteristics: the key to universal.
- Mounting position: the cabinet front door, back door and side door.

ORDERING INFORMATION

PART NUMBER	DESCRIPTION
TL-CAC-LK	Cabinet Lock

Digital Temperature Unit



Features

- Power supply: 85-265VAC.
- Sensor: International cu50 resistance.
- Measuring range: -20—80.
- Measurement accuracy: 1.0(+/-1.0%).
- Sampling rate: 2/second.
- Output form: double relays(one group for master control, another one for alarm).
- Sensor's differential gap adjustable.
- Sensor support open circuit alarm.
- Power consumption: <5W.
- Ambient temperature: -10-50

ORDERING INFORMATION

PART NUMBER	DESCRIPTION
TL-CAC-DTU	Digital Temperature Unit

Power Distribution Unit



Features

- Power supply: 85-265VAC.
- 6 Way, 10 Way, 12 Way
- 13 Amps, 16 Amps, 32 Amps
- Industrial PDU's are also available.

ORDERING INFORMATION

PART NUMBER	DESCRIPTION
TL-CAC-PDU6	6 Way PDU, 1U, 2 Meter Cable
TL-CAC-PDU10	10 Way PDU, 1U, 2 Meter Cable
TL-CAC-PDU12	12 Way PDU, 1U, 2 Meter Cable